



Limix answer of Insulating problems

LIMIX Plasticoat 140

Description As an acrylic copolymer based, one-component; can be applied to all surfaces, it is resistant to water and humidity.

Usage Area LIMIX Plasticoat 140 is an ideal for joint slit, tile adhesive, sealant, calk and spackle.

Advantages After the complete drying, LIMIX PlastiCoat 140 becomes waterproof, good elasticity and resistant to all weather conditions.

LIMIX Plasticoat 140 is flexible, and maintains its flexibility between - 20 °C and +70 °C.

LIMIX Plasticoat 140 is environmental friendly compound.

Applications LIMIX Plasticoat 140 must be applied on clean, dust & grease free surface.



LIMIX Plasticoat 140 must be applied over 5 °C C with Max. 70 % environmental humidity.

LIMIX Plasticoat 140 stiffens enough to allow traffic after 24 hours.

Specifications

Solid content	80 ± 2 %
Viscosity	16000 ± 2000 mPas (CPs) @ 25 °C
Color	Creamy
Density	Approx. 1.80 g/cm ³
Solvent	water
Shelf life	In sealed package 9 month, keep from freeze.

Packaging Available as 5, 12, 30 kg packaging.

LIMIX Plasticoat 140
A new type of insulation material for water proofing

This data is based on our present knowledge. However, it shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.